



GANDUS NICO DR 580

INDUSTRIAL SEMI AUTOMATIC
CONSTANT HEATED SEALER
FOR MEDIUM AND LARGE DIMENSIONS BAGS

INDUSTRIAL SEMI AUTOMATIC CONSTANT HEATED SEALER FOR MEDIUM AND LARGE DIMENSIONS BAGS.

APPLICATIONS

DESIGNED FOR MEDIUM AND LARGE DIMENSIONS BAGS.

SEAL

SEAL LENGTH MM 580: SEALING WIDTH 30 MM.

DIGITAL THERMO-REGULATOR TO KEEP A STEADY SEALING TEMPERATURE.

SEPARATE SEALING TIME AND PRESSURE CONTROLS.

MECHANICAL PRESSURE ADJUSTMENT.

FEATURES

ADJUSTABLE HEAD HEIGHT.

SUPPLIED MOUNTED ON A STAND AND INDEPENDENT LOCKING CASTORS, COMPLETE WITH ADJUSTABLE WORK SURFACE.

ELECTRICAL FOOT SWITCH.

ADJUSTABLE IN HEIGHT WORK TABLE.

CODING SYSTEM

ALSO AVAILABLE WITH CODE EMBOSsing SYSTEM.

VERSATILITY

IT CAN BE SYNCHRONIZED TO DOSING SYSTEMS TO CREATE AN EFFICIENT COMPLETE PACKAGING LINE, PERFECT FOR MEDIUM PRODUCTION RUNS.

VERSIONS

EPOXY PAINTED STEEL VERSION.

STAINLESS STEEL VERSION.

ACCESSORIES UPON REQUEST

CODE EMBOSsing SYSTEM TO EMBOSs DATES OR BATCH NUMBERS ON THE SEAL AREA

RL 200 INDEPENDENT GRAVITY ROLLER

S-20 ADJUSTABLE PRODUCT TRAY



GANDUS NICO DR 580

INDUSTRIAL SEMI AUTOMATIC

CONSTANT HEATED SEALER

FOR MEDIUM AND LARGE DIMENSIONS BAGS

TECHNICAL DATA

NICO DR 580

MATERIALS	PP, PA/PE, AL/PE, POLYESTER/PE
SEALING PROCESS	CONSTANT HEATED
SEALING BARS	LOWER AND UPPER, KNURLED
SEAL	MM 580 x 30
TEMPERATURE	0° ÷ 250° C ± 3%
TEMPERATURE CONTROL	ELECTRONIC THERMOREGULATOR 0° - 250°C
SEALING TIME CONTROL	MEDIANTE TEMTIMER 0 - 12 SEC.
REGOLAZIONE PRESSIONE	MECANICAL
CODING SYSTEM (OPTION)	12 CHARACTERS
AVERAGE PRODUCTIVITY	300 BAGS
POWER	V 220 - Hz 50 - SINGLE PHASE
MAX ABSORPTION	Kw 1,7
DIMENSIONS AND WEIGHT	MM 800 x 640 x 1620 - KG 110
CONSTRUCTION	CE RULES
ACCESSORIES UPON REQUEST	EMBOSSING CODING SYSTEM, MAX. 12 DIGITS - COMPLETE WITH STANDARD SET 57 DIGITS FOR DATA + LOT CODING (I.E.: JAN 12-L365)
	ADDITIONAL DIGITS
	S-20 90° ADJUSTABLE PRODUCT TRAY
	RL 200 INDEPENDENT GRAVITY ROLLER MM 2000 x 500