



GANDUS XS TUBE

FFS PACKAGING MACHINE FROM LAYFLAT TUBE
VERSATILE, ERGONOMIC, OPERATOR'S FRIENDLY
STAINLESS STEEL VERSION AVAILABLE

TAILORED TECHNOLOGY
TO OVERCOME THE TOUGHEST CHALLENGES

TUBULAR PACKAGING MACHINE, DESIGNED AND MANUFACTURED FOR ALL TYPES OF NEUTRAL OR PRINTED LDPE FILMS, WITH ANTISTATIC TREATMENT.

DEVELOPED FOR ALL APPLICATIONS THAT REQUIRE BOTH MAXIMUM SPEED AND SIMPLICITY IN FORMAT CHANGEOVER.

USE OF REELS OF DIFFERENT WIDTHS, WITHOUT PARTS DISASSEMBLY OR SETTINGS MODIFICATION.

AUTOMATIC FORMING OF THE BAG WITH OPENING UPWARDS.

BAG FILLING AND SUBSEQUENT SEALING ARE CARRIED OUT IN MANUAL BY STARTING THE MACHINE CYCLE BY BUTTON, OR AUTOMATICALLY.

RAPID REEL CHANGE, ONLY FEW SECONDS.

ACTIVATION BAG CLOSURE IN MANUAL MODE FROM START PUNCH BUTTON WITH A MAGNETIC BASE TO ALLOW ITS PLACING IN THE MOST CORRECT POSITION.

APPLICATIONS

ALL PRODUCTS REQUIRING MAXIMUM SPEED, SIMPLE INFEEED, EASY FORMAT CHANGEOVER.



ADVANTAGES AND BENEFITS

*ULTIMATE EFFICIENCY, SPEED, FLEXIBILITY, RELIABILITY
IN AUTOMATIC BAGGING OPERATIONS*

QUICK, EASY, ECONOMIC PACKAGING OF DIFFERENT TYPES, SIZES AND SHAPES OF PRODUCTS AND BAGS.

SAFE PACKAGING OF FRAGILE AND DELICATE PRODUCTS.

USE OF TUBULAR FILM, TO REDUCE THE COST OF BUYING AND STORING BAGS IN MANY DIFFERENT SIZES.

EASY PRODUCT INFEEED.

WITH "NO FALL", EVEN FRAGILE AND DELICATE PRODUCTS CAN BE SAFELY PACKED.

INTEGRATION WITH FILLING SYSTEMS, PICK AND PLACE, PRINTING SYSTEMS, LABELLING MACHINES.

CUSTOMIZATION AT THE HIGHEST LEVELS.



GANDUS XS TUBE

FFS PACKAGING MACHINE FROM LAYFLAT TUBE
VERSATILE, ERGONOMIC, OPERATOR'S FRIENDLY
STAINLESS STEEL VERSION AVAILABLE

TAILORED TECHNOLOGY TO OVERCOME THE TOUGHEST CHALLENGES

NEW IN

- CUSTOMIZABLE OPTION ACCESS PASSWORD FOR DATA MODIFICATION TO ENSURE THAT ONLY AUTHORIZED PERSONNEL CAN MAKE CHANGES, KEEPING SYSTEM OR DATA SECURE AND PRESERVING INTEGRITY AND RELIABILITY.
- REVAMPED GRAPHICAL INTERFACE WITH ICON BASED MENU, MACHINE FUNCTION DIAGNOSTICS AND CONTROL, UP TO 500 RECIPES, UP TO 40 OPERATORS (OPTION), REMOTE ACCESS (OPTION).

DIGITAL TOUCH SCREEN CONTROL DISPLAY

EASY SETTING OF ALL PRODUCTION SETTINGS AND PARAMETERS.


CHOICE OF LANGUAGE.

EASY AND PUNCTUAL SELECTION OF VALUES TO BE SET.

POSSIBILITY TO SAVE DIFFERENT WORK CONFIGURATIONS FOR IMMEDIATE ACCESS TO EVERY SINGLE JOB.

STANDARD EQUIPMENT

- CHECK THROUGH PLC AND FUNCTIONING DIAGNOSTIC ON COMMAND KEYBOARD
- SEALING BARS WITH MECHANICAL CLOSURE EQUIPPED WITH SAFETY DEVICE
- CONSTANTLY THROUGH PANEL ADJUSTABLE SEALING BARS PREHEATING
- OPENING SYSTEM FOR SMALL AND LIGHT BAGS
- IMMEDIATE CHANGE OF BAG LENGTH WITH CONTINUOUS ADJUSTMENT (FROM 80 TO 999 MM) FROM PANEL
- PRESELECTED BAG QUANTITY READER, WITH STOP WHEN THE PRESET NUMBER IS REACHED
- FUNCTION OF EMPY AND ON ONE SIDE OPEN BAGS PRODUCTION
- SELECTOR OF BAG GRIP JAWS INSERTION TO VARY THE INFEEED MOUTH
- WHEEL PUNCHER WITH 3 DIFFERENT DRILLING POSITIONS: RIGHTS, LEFT, CENTER.
- COUNTER
- INCLINED SLIDE
- MAGNETIC START BUTTON



SAFETY

GANDUS XS TUBE ARE EQUIPPED WITH A PROTECTIVE PLEXIGLAS BARRIER.

GANDUS XS TUBE

FFS PACKAGING MACHINE FROM LAYFLAT TUBE
VERSATILE, ERGONOMIC, OPERATOR'S FRIENDLY
STAINLESS STEEL VERSION AVAILABLE

TAILORED TECHNOLOGY TO OVERCOME THE TOUGHEST CHALLENGES

KIND OF PRODUCED BAGS

BAGS WITH ONE OR TWO SEALINGS
BAGS WITH MORE SEALINGS
PACKAGINGS WITH EUROHOLE
POSSIBILITY OF EMPTY BAGS PRODUCTION TO BE USED OFFLINE.

ACCESSORIES

IN ADDITION TO THE STANDARD EQUIPMENT, A WIDE AND COMPLETE RANGE OF ACCESSORIES ARE AVAILABLE ON REQUEST, TO ALLOW THE UTMOST CUSTOMIZATION OF THE MACHINE.

VERSIONS

- STANDARD VERSION
- STAINLESS STEEL VERSION
- POSSIBILITY OF **SYNCHRONIZATION** WITH OTHER DEVICES.


PACKAGING MATERIALS

GANDUS MATERIALS DIVISION OFFERS TOP NOTCH TUBULAR FILM SELECTED TO GUARANTEE MAX PRODUCT PROTECTION AND PERFECT INTEGRATION WITH GANDUS XS TUBE PACKAGING MACHINE.

MATERIALS ARE AVAILABLE IN STOCK IN DIFFERENT SIZES, OR CAN BE ORDERED ON REQUEST.

AVAILABLE NEUTRAL, WITH CENTRAL WHITE BAND OR CUSTOM PRINT.

THE MOST EFFICIENT WAY TO QUICKLY AND EASILY ACHIEVE THE HIGHEST STANDARDS OF OPERATIONAL EFFICIENCY, COST REDUCTION AND PACKAGING QUALITY.



GANDUS XS TUBE

FFS PACKAGING MACHINE FROM LAYFLAT TUBE
VERSATILE, ERGONOMIC, OPERATOR'S FRIENDLY
STAINLESS STEEL VERSION AVAILABLE

TAILORED TECHNOLOGY TO OVERCOME THE TOUGHEST CHALLENGES

TECHNICAL FEATURES	XS TUBE 300	XS TUBE 500
REEL WIDTH	MM 80 - 300	MM 100 - 500
BAGS LENGTH	MM 80 - 999	MM 80 - 999
REEL MATERIAL	LDPE TUBULAR THICKNESS MM 0.06—0.13	LDPE TUBULAR THICKNESS MM 0.06—0.13
EXTERNAL REEL DIAMETER INNER REEL DIAMETER	MM 300 MM 55/75	MM 300 MM 55/75
FRAME	PAINTED STEEL (INOX UPON REQUEST)	PAINTED STEEL (INOX UPON REQUEST)
SAFETY SENSORS	ELECTROMECHANICAL	ELECTROMECHANICAL
CYCLES/MIN	UP TO A 15 ACCORDIG TO BAG LENGTH AND OPTIONALS	UP TO A 12 ACCORDING TO BAG LENGTH AND OPTIONALS
MOUTH OPENING ADJUSTMENT	FROM TOUCH SCREEN	FROM TOUCH SCREEN
BAS EXIT POSITION	ADJUSTABLE	ADJUSTABLE
CONTROL DISPLAY	TOUCH SCREEN	TOUCH SCREEN
MAX REEL WEIGHT	Kg 15	Kg 22
ELECTRICAL POWER	230 V SINGLE PHASE + EARTH	230 V SINGLE PHASE + EARTH
PNEUMATIC	0.6 MPA (6 BAR) NON LUBRICATED AIR	0.6 MPA (6 BAR) NON LUBRICATED AIR
AIR CONSUMPTION	AVERAGE VALUE~0,008 m ³ /CYCLE (~8 L/CYCLE) MAX VALUE ~0,012 m ³ /CYCLE (~12 L/CYCLE)	AVERAGE VALUE~0,010m ³ /CYCLE MAX VALUE ~0,015m ³ /CYCLE
POWER	Kw 2 WITHOUT ACCESSORIES	Kw 2 WITHOUT ACCESSORIES
DIMENSIONS	MM 1150 x 830 x 1000	MM 1565 x 890 x 1050
WEIGHT	Kg 130	Kg 150

E&OE

TECHNICAL MODIFICATIONS RESERVED 05/2025