



DN 350

IMPULSE SEALER FOR
MEDICAL POUCHES AND REELS.
ACCORDING TO DIN 58953-7

IMPULSE SEALER FOR MEDICAL POUCHES AND REELS ACCORDING TO DIN 58953-7.

ESPECIALLY DESIGNED FOR MEDICAL AND DENTAL SURGERIES AND LABORATORIES.

THE SEALING JAWS ARE SIMPLY CLOSED BY HAND AND HELD ELECTROMAGNETICALLY.

THIS MAKES THE OPERATION FASTER AND WITHOUT THE NEED FOR ANY LEVER.

AT THE END OF THE CYCLE THE JAWS AUTOMATICALLY OPEN WITHOUT HAVING TO WAIT FOR ANY ACOUSTIC OR OPTICAL SIGNALS.

SEALING AND COOLING TIME ARE SET BY THE OPERATOR AND CONTROLLED BY AN ELECTRONIC TIMER.

IT COMES COMPLETE WITH A ROLL HOLDER AND CUTTING DEVICE.

ADVANTAGES & BENEFITS

THE MODEL DN 350, FULLY COMPLIES WITH DIN 58953-7 STANDARDS.

8 MM WIDE FLAT SEAL GUARANTEES A PERFECT SEAL STRENGTH WITH AN EASY, SAFE AND EFFECTIVE PEELABILITY.

DISTANCE SEALING-MEDICAL PRODUCT MM ≥ 30 DIN RULES.

SUITABLE FOR THE SEALING OF PRE-MADE STERILE BARRIER SYSTEMS FOR STEAM STERILIZERS.

DESIGNED AND MANUFACTURED TO ENABLE PROCESS OPTIMIZATION, FULLY RESPECTING TOP QUALITY AND ENERGY SAVING EFFICIENCIES.

ACCESSORIES

- FRONT SUPPORT TRAY
- ROLL-HOLDER WITH CUTTING DEVICE (INCLUDED)



DN 350

IMPULSE SEALER FOR
MEDICAL POUCHES AND REELS.
ACCORDING TO DIN 58953-7

TECHNICAL DATA

GENERAL FEATURES

PAINTED STEEL FRAME
ADJUSTABLE FREE EDGE
BUILT-IN CUTTING DEVICE

SEALING

IMPULSE SEALING
KIND OF SEALING—FLAT
SEALING WIDTH 8 MM
SEALING LENGTH 350 MM
DISTANCE SEALING-MEDICAL PRODUCT MM ≥ 30 DIN RULES

MATERIALS

POUCHES/REELS EN 868-5
PAPER POUCHES EN 868-4
GUSSETED POUCHES/REELS
PP POUCHES
HEADER BAGS
POLYETHYLENE

CONTROLS

TIME CONTROL

PARAMETERS

SEALING TIME (SEC.)

TECHNICAL DATA

COMPLIANCES

UNI EN 868-5:2009
DIN 58953-7
DIRECTIVES 2006/42/EC—2014/30/EU-2014/35/EU
MANUFACTURED IN A UNI EN ISO 9001:2015 QUALITY
SYSTEM CERTIFIED COMPANY

FUNCTIONS

TIME SETTING
ENERGY SAVING

POWER SUPPLY

POWER SUPPLY 100; 110/115; 230/240 VAC SINGLE PHASE
MULTI FREQUENCY; FREQUENCY 50/60 Hz
MAX POWER 900 W

ACCESSORIES

FRONT SUPPORT TRAY
ROLL HOLDER (INCLUDED)

SERVICES

SEAL STRENGTH TEST EN 868-5
MAINTENANCE
DIMENSIONS / WEIGHTS
DIMENSIONS 439x311x175 MM / WEIGHT 18 Kg