



MINIRÒ POLY

TABLE TOP ROTARY SEALER
FOR PE, PP, TYVEK[®]
AND HEAT SEALABLE LAMINATED MATERIALS
VALIDATABLE VERSION AVAILABLE

TABLE TOP ROTARY SEALER FOR PE, PP, PP/PA, PA/PA, TYVEK AND FOR OTHER HEAT SEALABLE LAMINATED MATERIALS POUCHES.

EXTERNAL PRINT SYSTEM AVAILABLE.

SEALING WIDTH 9 MM.

SPEED 6MT/MIN.

TEMPERATURE ADJUSTMENT.

LCD 2 LINES 16 CHRTS.

VERSIONS

STANDARD VERSION

VP VERSION, FULLY VALIDATABLE ACCORDING TO ISO 11607-2 STANDARD, FOR PHARMA AND MEDICAL INDUSTRY.

SAFETY

A 9 MM WIDE KNURLED SEAL GUARANTEES A PERFECT SEAL STRENGTH WITH EASY AND SAFE PEELABILITY.

PACKAGING

PERFECTLY SUITABLE FOR PE, PP, COATED MATERIAL, BAGS WITH HEADER CARDS.

THE VALIDATABLE MODEL MINIRÒ H-POLY VP *Evo* IS SUITABLE FOR THE SEALING LDPE POUCHES, HEADER BAGS AND OTHER ALL KNOWN, SEALABLE, PRE-MADE STERILE BARRIER SYSTEMS, UNCOATED TYVEK[®].

HI - HUMAN INTERFACE

THE MODEL MINIRÒ POLY IS EQUIPPED WITH A 16 CHARACTERS ON 2 LINES DIGITAL DISPLAY AND A WIDE AND CLEAR KEYBOARD.

CLEANING AND DISINFECTION

STAINLESS STEEL TOP COVER ALLOWS AN EASY AND EFFECTIVE CLEANING AND DISINFECTION.

PRINT FACILITY

EXTERNAL PRINT SYSTEM AVAILABLE.

ENERGY SAVING

ALL GANDUS MEDICAL SEALERS ARE DESIGNED AND MANUFACTURED TO ENABLE PROCESS OPTIMIZATION, FULLY RESPECTING ENERGY SAVING EFFICIENCIES.

ACCESSORIES

INDEPENDENT MOTORIZED CONVEYOR

PS 654 FRONT SUPPORT TRAY

RL 80 FRONT ROLLER SUPPORT TRAY



MINIRÒ POLY

TABLE TOP ROTARY SEALER
FOR PE, PP, Tyvek[®]
AND HEAT SEALABLE LAMINATED MATERIALS
VALIDATABLE VERSION AVAILABLE

TECHNICAL DATA

GENERAL FEATURES

AISI 304 STAINLESS STEEL COVER
PAINTED STEEL FRAME
BUILT-IN ADJUSTABLE GUIDE
ADJUSTABLE FREE EDGE 0÷32 MM
MEMBRANE KEYBOARD FLEX STRIP
LCD 2 LINES 16 DIGITS
SEALING
ROTARY SEALING
KIND OF SEALING: KNURLED, FLAT AS OPTION
SEALING HEIGHT 9 MM
SEALING LENGTH UNLIMITED
DISTANCE SEALING-MEDICAL PRODUCT MM ≥ 30 DIN RULES
HEAT SEALABLE MATERIALS
PE / PP PP/PA / Tyvek / LAMINATED AL
CERTIFICATIONS/SAFETY
DIN 58953-7
DIRECTIVE 2006/42/EC-2014/30/EU-2014/35/EU
MANUFACTURED IN A UNI EN ISO 9001:2015 QUALITY SYSTEM
CERTIFIED COMPANY

TECHNICAL DATA

PARAMETERS

SEALING SPEED 6 MT/MIN
TEMPERATURE ADJUSTMENT 10°C- 220°C
TEMPERATURE TOLERANCE $\pm 1\%$

HIGH TEMPERATURE ALARM
LOW TEMPERATURE ALARM

FUNCTIONS

MULTILANGUAGE MENU
AUTOMATIC SEALING PRESSURE ADJUSTMENT
COUNTER (OPTION)

INTERNAL PROBE

SELF DIAGNOSTICS

POWER SUPPLY

POWER SUPPLY 110/115; 230/240 VAC SINGLE PHASE
FREQUENCY 50/60 Hz
ABSORPTION 500 W

DIMENSIONS / WEIGHTS

DIMENSIONS 554x270x237 MM
WEIGHT 18 Kg

