



REBI^TECH RT 230 TOUCH

ROTARY MEDICAL SEALERS

CRAFT YOUR PERSONAL TOUCH SEALING SOLUTION

WITH OUR UTMOST EASY
AND COMPLETE CUSTOMIZATIONS

CRAFT YOUR SPECIFIC PERSONAL MACHINE WITH GANDUS COMPACT, FLEXIBLE USER FRIENDLY ROTARY HEAT SEALERS, OFFERING NUMEROUS HIGHLY CUSTOMIZED VERSIONS TO MEET MOST DIVERSE PACKAGING NEEDS. DESIGNED AND MANUFACTURED ACCORDING TO CUTTING-EDGE TECHNOLOGICAL STANDARDS, FOR OPTIMAL RESPONSE TO ALL NEEDS OF HIGH PRODUCTION, RELIABILITY AND EASE OF USE.

SEALING MM 12, ROTARY, MULTI-LINE, ACCORDING TO DIN 58953.7: 2010.

SEALING SPEEDS ON REQUEST 6MT/MIN, 8MT/MIN, 10MT/MIN.

HEAT SEALABLE MATERIALS: ALL SEALABLE STERILE BARRIER SYSTEMS, AS WELL AS ALL NEW GENERATION PACKAGING MATERIALS.

BENEFITS AND ADVANTAGES

EASY UTMOST CUSTOMIZATION

SIMPLY START FROM REBI^TECH BASIC MODEL AND CHOOSE AMONG NUMBERLESS OPTIONS AND ACCESSORIES TO UPGRADE IT AND REACH THE HIGHEST LEVELS OF MACHINE CUSTOMIZATION TO PERFECTLY MATCH YOUR MOST SPECIFIC NEEDS.

NUMBERLESS OPTIONS TO ASSURE PERFECT MATCHING WITH YOUR SPECIFIC REQUIREMENTS

EXPLORE OUR LIST OF OPTIONS AND ACCESSORIES TO CONFIGURE YOUR PERSONAL REBI^TECH SEALER.

STARTING FROM BASIC MODEL YOU ADD EXACTLY WHAT YOU NEED AND YOU ONLY PAY EXACTLY WHAT YOU NEED.

INTERNATIONAL STANDARDS COMPLIANCES

NEW GENERATION HARDWARE AND SOFTWARE TO GUARANTEE ACCURATE CONTROL OF SEALING PARAMETERS AND ENSURE MAXIMUM COMPLIANCE WITH ISO 11607.2 STANDARDS AND INTERNATIONAL GUIDELINES EN-ISO TS 16775.

SAFETY

MULTI-LINE MM 12 SEALING GUARANTEES IDEAL SEALING, FOR EASY AND SAFE PEELABILITY.

AUTOMATIC STAND BY AND AUTOMATIC START WITH MICROPROCESSOR CONTROL.

USER FRIENDLY OPERATOR'S INTERFACE

WETHER WITH A POLYCARBONATE KEYBOARD AND CLEAR LCD OR A 4.3" COLOUR TOUCH SCREEN, THE QUICK AND SIMPLE SETTING MENU ALLOWS AN EASY READING OF SET DATA AND OPERATION.

ENERGY SAVING

DESIGNED AND MANUFACTURED TO ALLOW PROCESS OPTIMIZATION IN FULL COMPLIANCE WITH ENERGY SAVING EFFICIENCIES.

REBI^TTECH RT 230 TOUCH

ROTARY MEDICAL SEALERS

CRAFT YOUR PERSONAL TOUCH SEALING SOLUTION

WITH OUR UTMOST EASY AND COMPLETE CUSTOMIZATIONS

OPTIONS

GANDUS REBI^TTECH NUMBERLESS OPTIONS ALLOW AN UTMOST SEALER CUSTOMIZATION, TO CRAFT YOUR PERSONAL MACHINE AND MEET ANY MOST SPECIFIC PACKAGING REQUIREMENT.

BUILT-IN PRINT SYSTEM - 9 DOT MATRIX

VALIDATION PACKAGE (USB TRACEABILITY)

VALIDATION PACKAGE (USB) AND INTEGRATED PRINTER

VALIDATION PACKAGE (USB) AND COMPUTER INTERFACE (ADDITIONAL RS 232)

4.3" COLOUR TOUCH SCREEN OPERATOR'S INTERFACE

LABEL PRINTER

SECURSCAN BARCODE

FLAT SEALING

CALIBRATION CERTIFICATES

ACCESSORIES

FRONT TRAY REBI^TTECH SERIE

PR-H40 ROLL HOLDER WITH CUTTING DEVICE 1 LEVEL

PR-H50 ROLL HOLDER WITH CUTTING DEVICE 2 LEVELS

COMPLIANCES*

UNI EN ISO 11607-2

UNI EN 868-5:2019

EN ISO TS 16775

DIN 58953-7

DIRECTIVES 2006/42/EC-2014/30/UE-2014/35/UE

UNI/TR 11408:2011

MEMO 5 STERILIZATION GUIDELINES

MANUFACTURED IN A UNI EN ISO 9001:2015 QUALITY SYSTEM CERTIFIED COMPANY

* ACCORDING TO OPTIONS

REBITeCH RT 230 TOUCH

ROTARY MEDICAL SEALERS

CRAFT YOUR PERSONAL TOUCH SEALING SOLUTION
WITH OUR UTMOST EASY AND COMPLETE CUSTOMIZATIONS

TECHNICAL FEATURES *

GENERAL FEATURES

ROTARY SEALING

COLOUR 4,3" TOUCH SCREEN

AISI 304 STAINLESS STEEL COVER

PAINTED STEEL FRAME

BUILT-IN ADJUSTABLE GUIDE

SEAL DISTANCE FROM THE EDGE MM 0-35

SEALING WIDTH 12 MM

AVAILABLE SEALING SPEED 6MT/MIN, 8 MT/MIN; 10 MT/MIN

TEMPERATURE ADJUSTMENT 10-220°C MONITORED

TEMPERATURE TOLERANCE $\pm 1\%$

SWITCH OFF TOLERANCE $\pm 5^{\circ}\text{C}$ (DIN 58953-7)

SEALING PRESSURE FIX—MONITORED*

MULTILANGUAGE MENU

MICROPROCESSOR CONTROLLED

STARTING PHOTOCCELL

AUTOMATIC START/STAND BY

AUTOMATIC SEALING PRESSURE ADJUSTMENT

USB/RS 232 INTERFACES*

PIECE COUNTER*

POWER V 100/115 - Hz 50/60 – SINGLE PHASE

POWER V 230/240 - Hz 50/60 – SINGLE PHASE

AVERAGE POWER CONSUMPTION 150W**

DIMENSIONS AND WEIGHT MM 473x235x181 / KG 12,5

TECHNICAL FEATURES *

HEAT SEALABLE MATERIALS

SEALABLE PAPER BAGS ACC. TO EN ISO 11607-1/EN 868-4

SEALABLE POUCHES AND REELS ACC. TO EN ISO 11607-1/EN 868-5 MADE OF FILM AND PAPER ACC. TO EN 868-3

SEALABLE POUCHES AND REELS ACC. TO ISO 11607-1/EN 868-5 MADE OF FILM AND UNCOATED MATERIALS MADE OF POLYOLEFINS ACC. TO EN 868-9 (EG TYVEK®)

TRACEABILITY

SAVING ON REMOVABLE PEN DRIVE VIA USB PORT OF ALL SENSITIVE DATA RELATED TO EACH SEALED POUCH

SEALING DATE AND TIME

MACHINE ID; POUCH ID

SEALING TEMPERATURE; SEALING STRENGTH

TRANSPORT SPEED

BATCH; OPERATOR

ALARM CODES

ALARMS AND SAFETY

HIGH TEMPERATURE ALARM WITH LOCK FUNCTION

LOW TEMPERATURE ALARM WITH LOCK FUNCTION

MACHINE INTERNAL TEMPERATURE CONTROL PROBE

DIAGNOSTICS MACHINE COMPONENTS

COMPLIANCES

EN ISO 11607-2

DIN 58953.7

UNI EN 868-5

2006/42/CE-2014/30/UE-2014/35/UE

STERILIZATION GUIDELINES-MEMO 5

PRODUCED IN A COMPANY CERTIFIED WITH UNI EN ISO 9001:2015 QUALITY SYSTEM

ACCESSORIES

FRONT SUPPORT TRAY

PR H40/H50 ROLL HOLDER WITH CUTTING DEVICE

PRN 2000 LABELS PRINTER

E&OE; Technical modifications reserved 05/2025

* ACCORDING TO OPTIONS

**MAY VARY DURING HEATING UP PHASE

REBITeCH RT 230 TOUCH

YOUR PERSONAL TOUCH SEALING SOLUTION