



REBiTECH RT 230 Touch

ROTARY MEDICAL SEALERS

CRAFT YOUR PERSONAL TOUCH SEALING SOLUTION

WITH OUR UTMOST EASY
AND COMPLETE CUSTOMIZATIONS

CRAFT YOUR SPECIFIC PERSONAL MACHINE WITH GANDUS COMPACT, FLEXIBLE USER FRIENDLY ROTARY HEAT SEALERS, OFFERING NUMEROUS HIGHLY CUSTOMIZED VERSIONS TO MEET MOST DIVERSE PACKAGING NEEDS. DESIGNED AND MANUFACTURED ACCORDING TO CUTTING-EDGE TECHNOLOGICAL STANDARDS, FOR OPTIMAL RESPONSE TO ALL NEEDS OF HIGH PRODUCTION, RELIABILITY AND EASE OF USE.

SEALING MM 12, ROTARY, MULTI-LINE, ACCORDING TO DIN 58953.7: 2010.

SEALING SPEED ON REQUEST 6MT / MIN, 8MT / MIN, 10MT / MIN.

HEAT SEALABLE MATERIALS: ALL SEALABLE STERILE BARRIER SYSTEMS, AS WELL AS ALL NEW GENERATION PACKAGING MATERIALS.

BENEFITS AND ADVANTAGES

EASY UTMOST CUSTOMIZATION

SIMPLY START FROM REBiTECH BASIC MODEL AND CHOOSE AMONG NUMBERLESS OPTIONS AND ACCESSORIES TO UPGRADE IT AND REACH THE HIGHEST LEVELS OF MACHINE CUSTOMIZATION TO PERFECTLY MATCH YOUR MOST SPECIFIC NEEDS.

NUMBERLESS OPTIONS TO ASSURE PERFECT MATCHING WITH YOUR SPECIFIC REQUIREMENTS

EXPLORE OUR LIST OF OPTIONS AND ACCESSORIES TO CONFIGURE YOUR PERSONAL REBiTECH SEALER. STARTING FROM BASIC MODEL YOU ADD EXACTLY WHAT YOU NEED AND YOU ONLY PAY EXACTLY WHAT YOU NEED.

INTERNATIONAL STANDARDS COMPLIANCES

NEW GENERATION HARDWARE AND SOFTWARE TO GUARANTEE ACCURATE CONTROL OF SEALING PARAMETERS AND ENSURE MAXIMUM COMPLIANCE WITH ISO 11607.2 STANDARDS AND INTERNATIONAL GUIDELINES EN-ISO TS 16775.

SAFETY

MULTI-LINE MM 12 SEALING GUARANTEES IDEAL SEALING, FOR EASY AND SAFE PEELABILITY.

AUTOMATIC STAND BY AND AUTOMATIC START WITH MICROPROCESSOR CONTROL.

USER FRIENDLY OPERATOR'S INTERFACE

WHETHER WITH A POLYCARBONATE KEYBOARD AND CLEAR LCD OR A 4.3" COLOUR TOUCH SCREEN, THE QUICK AND SIMPLE SETTING MENU ALLOWS AN EASY READING OF SET DATA AND OPERATION.

ENERGY SAVING

DESIGNED AND MANUFACTURED TO ALLOW PROCESS OPTIMIZATION IN FULL COMPLIANCE WITH ENERGY SAVING EFFICIENCIES.

REBITeCH RT 230 TOUCH

ROTARY MEDICAL SEALERS

CRAFT YOUR PERSONAL TOUCH SEALING SOLUTION

WITH OUR UTMOST EASY AND COMPLETE CUSTOMIZATIONS

OPTIONS

GANDUS REBITeCH NUMBERLESS OPTIONS ALLOW AN UTMOST SEALER CUSTOMIZATION, TO CRAFT YOUR PERSONAL MACHINE AND MEET ANY MOST SPECIFIC PACKAGING REQUIREMENT.

BUILT-IN PRINT SYSTEM - 9 DOT MATRIX

VALIDATION PACKAGE (USB TRACEABILITY)

VALIDATION PACKAGE (USB) AND INTEGRATED PRINTER

VALIDATION PACKAGE (USB) AND COMPUTER INTERFACE (ADDITIONAL RS 232)

4.3" COLOUR TOUCH SCREEN OPERATOR'S INTERFACE

LABEL PRINTER

SECURSCAN BARCODE

FLAT SEALING

CALIBRATION CERTIFICATES

ACCESSORIES

FRONT TRAY REBITeCH SERIE

PR-H40 ROLL HOLDER WITH CUTTING DEVICE 1 LEVEL

PR-H50 ROLL HOLDER WITH CUTTING DEVICE 2 LEVELS

CONFORMITIES*

UNI EN ISO 11607-2

UNI EN 868-5:2019

EN ISO TS 16775

DIN 58953-7

DIRECTIVES 2006/42/EC-2014/30/UE-2014/35/UE

UNI/TR 11408:2011

MEMO 5 STERILIZATION GUIDELINES

MANUFACTURED IN A UNI EN ISO 9001:2015 QUALITY SYSTEM CERTIFIED COMPANY

* ACCORDING TO OPTIONS

REBITeCH RT 230 TOUCH

ROTARY MEDICAL SEALERS

CRAFT YOUR PERSONAL TOUCH SEALING SOLUTION

With our utmost easy and complete customizations

| TECHNICAL FEATURES * | TECHNICAL FEATURES * |
|---|--|
| GENERAL FEATURES | HEAT SEALABLE MATERIALS |
| ROTARY SEALING | SEALABLE PAPER BAGS ACC. TO EN ISO 11607-1/EN 868-4 |
| COLOUR 4,3" TOUCH SCREEN | SEALABLE POUCHES AND REELS ACC. TO EN ISO 11607-1/EN 868-5 MADE OF FILM AND PAPER ACC. TO EN 868-3 |
| AISI 304 STAINLESS STEEL COVER | SEALABLE POUCHES AND REELS ACC. TO ISO 11607-1/EN 868-5 MADE OF FILM AND UNCOATED MATERIALS MADE OF POLYOLEFINS ACC. TO EN 868-9 (EG TYVEK®) |
| PAINTED STEEL FRAME | TRACEABILITY |
| BUILT-IN ADJUSTABLE GUIDE | SAVING ON REMOVABLE PEN DRIVE VIA USB PORT OF ALL SENSITIVE DATA RELATED TO EACH SEALED POUCH |
| SEAL DISTANCE FROM THE EDGE MM 0-35 | SEALING DATE AND TIME |
| SEALING WIDTH 12 MM | MACHINE ID; POUCH ID |
| AVAILABLE SEALING SPEED 6 MT/MIN; 8 MT/MIN; 10 MT/MIN | SEALING TEMPERATURE; SEALING STRENGTH |
| TEMPERATURE ADJUSTMENT 10-220°C MONITORED | TRANSPORT SPEED |
| TEMPERATURE TOLERANCE ± 1% | BATCH; OPERATOR |
| SWITCH OFF TOLERANCE ± 5°C (DIN 58953-7) | ALARM CODES |
| HEATING TIME: ≤ 10 SEC FROM STAND BY | ALARMS AND SAFETY |
| SEALING PRESSURE FIX—MONITORED* | HIGH TEMPERATURE ALARM WITH LOCK FUNCTION |
| MULTILANGUAGE MENU | LOW TEMPERATURE ALARM WITH LOCK FUNCTION |
| MICROPROCESSOR CONTROLLED | MACHINE INTERNAL TEMPERATURE CONTROL PROBE |
| STARTING PHOTOCCELL | DIAGNOSTICS MACHINE COMPONENTS |
| AUTOMATIC START/STAND BY | CONFORMITIES |
| AUTOMATIC SEALING PRESSURE ADJUSTMENT | EN ISO 11607-2 |
| USB/RS 232 INTERFACES* | DIN 58953.7 |
| PIECE COUNTER* | UNI EN 868-5 |
| POWER V 100/115 - Hz 50/60 – SINGLE PHASE | 2006/42/CE-2014/30/UE-2014/35/UE |
| POWER V 230/240 - Hz 50/60 – SINGLE PHASE | STERILIZATION GUIDELINES-MEMO 5 |
| AVERAGE POWER CONSUMPTION 150W** | PRODUCED IN A COMPANY CERTIFIED WITH UNI EN ISO 9001:2015 QUALITY SYSTEM |
| DIMENSIONS AND WEIGHT MM 473x235x181 / KG 12,5 | ACCESSORIES |
| | FRONT SUPPORT TRAY |
| | PR H40/H50 ROLL HOLDER WITH CUTTING DEVICE |
| | PRN 2000 LABELS PRINTER |

ERRORS/OMISSIONS EXCEPTED

* ACCORDING TO OPTIONS

* MAY VARY DURING HEATING UP PHASE

REBITeCH RT 230 TOUCH

YOUR PERSONAL TOUCH SEALING SOLUTION